

Checkweighers

TS310 Checkweigher

Overview

The TS310 range is for businesses requiring high levels of support for their end-of-line Checkweighing operation.

- Top quality touchscreen Operator interface
- Re-configurable round-frame mechanical design

Use

For use on continuous production lines. The machines are sealed to IP65 and constructed from stainless steel and food quality plastics. A highly innovative mechanical design means that in a matter of hours, the TS310 can be re-handed and modified on-site.

Operation

Operator Control:	12.1" Menu Driven TFT Display
Access Levels:	Password protected for Operators, Engineers and Supervisors
Set Up:	Menu Driven
Weight Range:	Up to 8Kg
Achievable Accuracy:	+/- 0.05%
Displayed Resolution:	1:12,000
Pack Speeds:	Up to 350 per minute

Construction Options

	Available
Reject Integrity Measures	Yes
Custom Top Covers	Yes
Air Blast Reject	Yes
Pneumatic Push Reject	Yes
Drop Flap Reject	Yes
Pneumatic Divert Reject	Yes
Side Locating Reject Collection Bin	Yes
Reject Collection Chute	Yes
Reject Collection Roller Track Conveyor	Yes
Salad (Wet Environment) Specification	Yes
Extended In-feed Conveyor	Yes
Extended Out-feed Conveyor	Yes

Management Information Support Options

	Available
Store 'n Print Statistics Collection Software	Yes
Statistics Analysis Utility	Yes
Management Information System	Yes
Printer	Yes
Remote Display	Yes
Remote Access via Ethernet and Web Page	Yes
Virtual Checkweigher	Yes

Control System

	Available
Selectable Weighing Regime (Minimum, emark, Mean Weight Tracking)	Standard
Trend-feedback to filler	Standard
Self Diagnostic Ability	Standard
Expandable Product Code Support (500 fitted as standard)	Yes

Services

Electrical Supply:	240V A/C, 110V A/C Or 50/60HZ single phase.
Air Supply:	6 bar clean and dry.

